

Pattern Recognition in Multispectral Satellite Images Using Concurrent Self-Organizing Modular Neural Networks

Prof. Dr. Victor-Emil Neagoe and Dr. Armand-Dragos Ropot

Faculty of Electronics, Telecommunications and Information Technology
'Politehnica' University of Bucharest, P.O. Box 16-37, RO-062510, Bucharest
Romania

victoremil@gmail.com

ABSTRACT

We investigate multispectral space image classification using the new artificial computational intelligence model called Concurrent Self-Organizing Maps (CSOM), representing a winner-takes-all collection of concurrent small modular self-organizing artificial neural networks. For comparison, we evaluate the performances of Bayes classifier. The implemented neural/statistical classifiers are evaluated using a LANDSAT TM image with 7 bands (multi-sensor data fusion) composed by a set of 7-dimensional pixels, out of which a subset contains labelled pixels, corresponding to seven thematic categories of Earth images taken from space. The best experimental result leads to the recognition rate of 95.29 %. The model has defence applications for Earth surveillance from space.

1.0 INTRODUCTION

The Self-Organizing Map (SOM) (also called Kohonen network) [2] is an artificial unsupervised network characterized by the fact that its neighbouring neurons develop adaptively into specific detectors of different vector patterns. Starting from the idea to consider the SOM as a cell characterizing a specific class only, we present and evaluate for space imagery the new neural recognition model called Concurrent Self-Organizing Maps (CSOM) [3], [4], [5]. CSOM represents a collection of small SOMs using a global competition strategy.

Processing of satellite imagery has wide applications for generation of various kinds of maps: maps of vegetation, maps of mineral resources of the Earth, land-use maps (civil or military buildings, agricultural fields, woods, rivers, lakes, and highways), and so on [1], [6]. The standard approach to satellite image classification uses statistical methods. A relative new and promising category of techniques for satellite image classification is based on neural models. We further evaluate the new neural CSOM model for recognition of multispectral satellite images by comparison with SOM and the well known Bayes statistical classifier (assuming normal classes).

The concluding remarks obtained as a result of the research on applying neural networks for classification of satellite imagery are the following:

- neural classifiers do not require initial hypotheses on the data distribution and are able to learn non-linear and discontinuous input data;
- neural networks can adapt easily to input data containing texture information;

| Report Documentation Page | | | | Form Approved OMB No. 0704-0188 | |
|--|------------------------------------|-------------------------------------|--|---|------------------------------------|
| Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. | | | | | |
| 1. REPORT DATE 01 DEC 2006 | | 2. REPORT TYPE N/A | | 3. DATES COVERED - | |
| 4. TITLE AND SUBTITLE Pattern Recognition in Multispectral Satellite Images Using Concurrent Self-Organizing Modular Neural Networks | | | | 5a. CONTRACT NUMBER | |
| | | | | 5b. GRANT NUMBER | |
| | | | | 5c. PROGRAM ELEMENT NUMBER | |
| 6. AUTHOR(S) | | | | 5d. PROJECT NUMBER | |
| | | | | 5e. TASK NUMBER | |
| | | | | 5f. WORK UNIT NUMBER | |
| 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Faculty of Electronics, Telecommunications and Information Technology Politehnica University of Bucharest, P.O. Box 16-37, RO-062510, Bucharest Romania | | | | 8. PERFORMING ORGANIZATION REPORT NUMBER | |
| 9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) | | | | 10. SPONSOR/MONITOR'S ACRONYM(S) | |
| | | | | 11. SPONSOR/MONITOR'S REPORT NUMBER(S) | |
| 12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited | | | | | |
| 13. SUPPLEMENTARY NOTES See also ADM202419., The original document contains color images. | | | | | |
| 14. ABSTRACT | | | | | |
| 15. SUBJECT TERMS | | | | | |
| 16. SECURITY CLASSIFICATION OF: | | | 17. LIMITATION OF ABSTRACT UU | 18. NUMBER OF PAGES 11 | 19a. NAME OF RESPONSIBLE PERSON |
| a. REPORT unclassified | b. ABSTRACT unclassified | c. THIS PAGE unclassified | | | |

Pattern Recognition in Multispectral Satellite Images Using Concurrent Self-Organizing Modular Neural Networks

- the neural classifiers are generally more accurate than the statistical ones;
- architecture of neural networks is very flexible.

2.0 CONCURRENT SELF-ORGANIZING MAPS (CSOM) FOR PATTERN CLASSIFICATION

Concurrent Self-Organizing Maps (CSOM) are a collection of small SOMs, which use a global *winner-takes-all* strategy. Each unit network (SOM) is used to correctly classify the patterns of one class only and the number of networks equals the number of classes. The CSOM *training* technique is a supervised one, but for any individual net the SOM specific training algorithm is used. We built “n” training patterns sets and we used the SOM training algorithm independently for each of the “n” SOMs. The CSOM model *for training* is shown in Figure 1.

For the recognition, the test pattern has been applied in parallel to every previously trained SOM. The map providing the least quantization error is decided to be the winner and its index is the class index that the pattern belongs to (see Figure 2).




Figure 1: The CSOM model (training phase)




Figure 2: The CSOM model (classification phase)

3.0 CSOM FOR CLASSIFICATION OF MULTISPECTRAL SATELLITE IMAGERY

3.1 Satellite Image Database

For training and testing the software of the proposed CSOM classification model as well as the classical SOM and the Bayes classifier (for comparison), we have used a LANDSAT TM image with 7 bands (Figures 3.a-g), having a number of 368,125 pixels (7-dimensional), out of which 6,331 pixels were classified by an expert into **seven thematic categories** (classes): *A- urban area*; *B-barren fields*, *C-bushes*, *D- agricultural fields*, *E-meadows*, *F- woods*, *G- water* (Figure 4).




Figure 3.a: Spectral band 1




Figure 3.b: Spectral band 2



Figure 3.c: Spectral band 3




Figure 3.d: Spectral band 4

Pattern Recognition in Multispectral Satellite Images Using Concurrent Self-Organizing Modular Neural Networks




Figure 3.e: Spectral band 5



Figure 3.f: Spectral band 6



Figure 3.g: Spectral band 7




Figure 4: Calibration image

3.2 Experimental Results of CSOM Satellite Image Classification

Each multispectral pixel (7 bands) is characterized by a corresponding 7-dimensional vector containing the pixel projections in each band. These vectors are applied to the input of the neural/statistical classifier. For classification, we have experimented the following neural versus statistical techniques:

- the new CSOM model
- the classical SOM classifier
- the Bayes classifier (by assuming the seven classes have normal repartitions).

The results of simulation are given in Tables 1-6. Two classified multispectral images are given in Figures 5 and 6 and the corresponding histograms are shown in Figures 7 and 8. The recognition rates for the training lot and also for the test lot are shown in Figures 9-10.




Figure 5: Classified multispectral pixels (7 categories) using a circular CSOM architecture with 7 x 112 neurons (recognition rate 95.29%)




Figure 6: Classified multispectral pixels (7 categories) using a circular SOM architecture with 784 neurons (recognition error 4.31 %)




Figure 7: Histogram of the classified multispectral LANDSAT TM image given in Figure 13 (using CSOM)




Figure 8: Histogram of the classified multispectral LANDSAT TM image given in Figure 14 (using SOM)

Pattern Recognition in Multispectral Satellite Images Using Concurrent Self-Organizing Modular Neural Networks

Table 1: Experimental results of multispectral satellite image classification with CSOM, SOM and Bayes classifiers (7 thematic classes; input vector space has the dimension 7)

| Nr | Type of classifier | Total number of neurons | Number of networks | Recognition score for the training lot (%) | Recognition score for the test lot (%) |
|----|---|-------------------------|--------------------|--|--|
| 1 | Circular CSOMs (7 x 112) | 784 | 7 | 98.71 | 95.29 |
| 2 | Circular SOM | 784 | 1 | 96.49 | 94.31 |
| 3 | Linear CSOMs (7 x 112) | 784 | 7 | 98.64 | 95.10 |
| 4 | Linear SOM | 784 | 1 | 97.06 | 94.12 |
| 5 | Rectangular CSOMs [7 x (14 x 8)] | 784 | 7 | 97.98 | 95.07 |
| 6 | Rectangular SOM (28 x 28) | 784 | 1 | 96.53 | 92.80 |
| 7 | Bayes classifier | | | 95.83 | 94.22 |

Table 2: Comparison of the best pixel classification scores obtained by SOM and CSOM for the training lot as a function of the number of neurons

| Number of neurons | | 49 | 98 | 196 | 392 | 784 | Bayes |
|----------------------|------|-------|-------|-------|-------|-------|-------|
| Recognition rate [%] | SOM | 91.60 | 93.53 | 95.10 | 95.86 | 97.06 | 95.83 |
| | CSOM | 93.27 | 95.01 | 96.62 | 97.76 | 98.71 | |

Table 3: Comparison of the best pixel classification scores obtained by SOM and CSOM for the test lot as a function of the number of neurons

| Number of neurons | | 49 | 98 | 196 | 392 | 784 | Bayes |
|----------------------|------|-------|-------|-------|-------|-------|-------|
| Recognition rate [%] | SOM | 92.04 | 93.87 | 93.62 | 94.34 | 94.31 | 95.17 |
| | CSOM | 92.86 | 94.79 | 93.71 | 94.85 | 95.29 | |

Pattern Recognition in Multispectral Satellite Images Using Concurrent Self-Organizing Modular Neural Networks

Table 4: Confusion matrix for the circular SOM with 784 neurons (test lot)

| Assigned Class | Real class | | | | | | | |
|---------------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|-------------|
| | A | B | C | D | E | F | G | Total [%] |
| A' | 80.00 | 0.08 | 1.97 | 0.00 | 0.00 | 0.21 | 0.62 | 1.96 |
| B' | 8.57 | 99.41 | 0.66 | 0.00 | 0.00 | 0.00 | 0.00 | 37.54 |
| C' | 5.71 | 0.17 | 73.68 | 0.33 | 0.48 | 4.95 | 3.73 | 4.80 |
| D' | 0.00 | 0.00 | 1.97 | 96.45 | 0.00 | 9.28 | 0.00 | 29.00 |
| E' | 0.00 | 0.00 | 0.66 | 0.00 | 98.55 | 0.00 | 0.00 | 6.48 |
| F' | 0.00 | 0.00 | 14.47 | 2.77 | 0.00 | 84.74 | 1.86 | 14.57 |
| G' | 5.71 | 0.08 | 4.61 | 0.00 | 0.00 | 0.41 | 93.79 | 5.21 |
| Unclassified | 0.00 | 0.25 | 1.97 | 0.44 | 0.97 | 0.41 | 0.00 | 0.44 |
| Total [%] | 2.21 | 37.54 | 4.80 | 28.50 | 6.54 | 15.32 | 5.09 | 100.00 |

Table 5: Confusion matrix for the circular CSOMs with (7 x 112) neurons (test lot)

| Assigned Class | Real class | | | | | | | |
|---------------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|-------------|
| | A | B | C | D | E | F | G | Total [%] |
| A' | 90.00 | 0.25 | 0.00 | 0.22 | 0.00 | 0.21 | 0.00 | 2.18 |
| B' | 2.86 | 99.58 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 37.44 |
| C' | 4.29 | 0.17 | 84.87 | 0.44 | 1.45 | 6.80 | 2.48 | 5.62 |
| D' | 0.00 | 0.00 | 1.32 | 95.79 | 0.00 | 6.39 | 0.00 | 28.34 |
| E' | 0.00 | 0.00 | 0.00 | 0.00 | 98.55 | 0.00 | 0.00 | 6.45 |
| F' | 0.00 | 0.00 | 5.26 | 3.55 | 0.00 | 85.77 | 0.00 | 14.41 |
| G' | 2.86 | 0.00 | 8.55 | 0.00 | 0.00 | 0.82 | 97.52 | 5.56 |
| Unclassified | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Total [%] | 2.21 | 37.54 | 4.80 | 28.50 | 6.54 | 15.32 | 5.09 | 100.00 |

Table 6: Training time required by the best SOM and CSOM as a function of the number of neurons (for multispectral pixel classification)

| Number of neurons | | 49 | 98 | 196 | 392 | 784 |
|---------------------|-------------|-----|-----|------|------|------|
| Training time [sec] | <i>SOM</i> | 276 | 545 | 1140 | 2040 | 4872 |
| | <i>CSOM</i> | 56 | 93 | 171 | 423 | 1020 |

Pattern Recognition in Multispectral Satellite Images Using Concurrent Self-Organizing Modular Neural Networks




Figure 9: Best pixel recognition rates on the training lot as a function of the total number of neurons




Figure 10: Best pixel recognition rates on the test lot as a function of the total number of neurons

4.0 CONCLUDING REMARKS

1. The new **CSOM** model uses a collection of small SOMs, each network having the task to correctly classify the patterns of one class only. The decision is based on a global *winner-takes-all* strategy.
2. We can evaluate the very good recognition score of multispectral satellite image classification for all the experimented classifiers, both neural ones (the new CSOM and the well-known SOM) and also

statistical (Bayes). However, the CSOM model leads to slightly better results for all the considered variants by comparison to SOM and Bayes.

3. The best results (a pixel classification rate of **95.29 %** for the test lot) are obtained using a CSOM model containing 7 circular SOMs with 112 neurons each of them. Taking into account the architecture variants for the components of CSOM, for this application the best variant is circular, followed by linear and then by rectangular.
4. The CSOM model requires a significantly less training time by comparison to the single SOM and Bayes.
5. The model has defence applications for Earth surveillance from space.

5.0 REFERENCES

- [1] Benediktsson, J.A., Swain, P.H. and Ersoy, O.K., *Neural Network Approaches versus Statistical Methods in Classification of Multisource Remote Sensing Data*, IEEE Trans. Geosci. Remote Sensing, vol. GE-28, no. 4, 1990, pp. 540-552.
- [2] Kohonen, T., *Self-Organizing Maps*, Springer- Verlag, Berlin, 1995.
- [3] Neagoe, V. and Ropot, A., *Concurrent Self-Organizing Maps for Pattern Classification*, Proceedings of First IEEE International Conference on Cognitive Informatics (ICCI2002), 19-20 August 2002, Calgary, Alberta, Canada, ISBN 0-7695-1726-9, pp. 304-312.
- [4] Neagoe, V. and Ropot, A., *Concurrent Self-Organizing Maps for Classification of Multispectral Satellite Imagery*, Proceedings of 6th World Multiconference on Systemics, Cybernetics and Informatics (SCI 2002), July 14-18 2002, Orlando, Florida, vol. XIV. ISBN 980-07-8147-1, pp. 126-131.
- [5] Neagoe, V. and Ropot, A., *A New Neural Approach for Pattern Recognition in Space Imagery*, NATO ARW on Data Fusion, Tallin, Estonia, June 27-July 1, 2005.
- [6] Neagoe, V. and Fratila, I., *A Neural Segmentation of Multispectral Satellite Images*, Computational Intelligence, Theory and Applications, (ed. B. Reusch), Springer, Berlin-New York, 1999, pp. 334-341.
- [7] DeWeert, M. J., *Fusion of Information from Disparate Electro-Optical Images for Maritime Surveillance*, NATO ARW on Data Fusion, Tallin, Estonia, June 27-July 1, 2005.

